

## SYSTEM SUMMARY STÅLPROFILSYSTEM

Item	SP 6000	SP 60000	SP 35000	SP 55000	SP 75000	SP 56500	SP 58000	SP 76500	SP 79000	SP 711000
Stainless	SP 96000		SP 95000	SP 955000	SP 975000	SP 956500	SP 958000	SP 976500	SP 979000	
Profile height	50/75/120	50/75/120	50	50	50	65	80	65	90	110
Thermal bridge	●	●	-	10	-	25	10	-	-	-
Fire resistance	-	-	-	-	10	-	-	25	50	2 x 25
Wall sections	●	●	E 30/E 60	●	E 30/E 60	●	●	EI 30/E 60	E 60/EI 60	EI 90
Door without midrail	-	-	EI 30/EI 60	●	EI 30/EI 60	●	●	EI 30/A 60/E 60	E 60/EI 60	-
Door with midrail	-	-	A 30	●	A 30	●	●	EI 30/A 60/E 60	E 60/EI 60	-
Window	-	-	E 30/E 60	●	E 30/E 60	●	●	EI 30/E 60	E 60/EI 60	-
Sliding door	-	-	E 30/EI 30/A 30	●	E 30/EI 30/A 30	●	●	EI 30	-	-
Arches	●	-	●	●	●	●	●	EI 30/A 60/E 60	E 60/EI 60	-
Rounded windows	-	-	●	●	●	●	●	EI 30	E 60/EI 60	-
Finger trap gasket	-	-	●	●	●	●	-	●	-	-
Module locks	-	-	●	●	●	●	●	●	●	-
Burglary resistant	-	-	CI 1-3	-	-	-	CI 1-3	-	-	-
Bullet proof	-	-	C1-C5 SF	C1-C5 SF	C1-C5 SF	C1-C5 SF	C1-C5 SF	C1-C5 SF	C1-C5 SF	-
U-value	●	●	-	-	-	●	-	●	●	-
Noise reduction	●	●	-	●	●	●	-	●	●	-

Note: The values for fire resistant and safety classes above are the maximums. Some constructions have lower fire resistant and safety classes. Fire resistant classes above comply with SITAC type approval certificates. Please refer to each systems catalogue for further details.